

AD-722 010  
Copy 2

21 APR 1971

NAVAL ORDNANCE LABORATORY  
LIBRARY

*Jimmy M. Naeff*  
*NOL*

**NOLTR** 71-2



FNOL3, A COMPUTER PROGRAM TO SOLVE  
ORDINARY DIFFERENTIAL EQUATIONS

By  
Ralph E. Ferguson  
Theodore A. Orlow

1 MARCH 1971

**NOL**

NAVAL ORDNANCE LABORATORY, WHITE OAK, SILVER SPRING, MARYLAND

ATTENTION

This document has been approved for  
public release and sale, its distribution  
is unlimited.

NOLTR 71-2

1900  
1901  
1902  
1903  
1904

1905 1906 1907 1908 1909

1910 1911 1912 1913 1914

1915  
1916  
1917

1918  
1919  
1920

FNOL3, A COMPUTER PROGRAM TO SOLVE ORDINARY DIFFERENTIAL EQUATIONS

Prepared by:

Ralph E. Ferguson and Theodore A. Orlow

ABSTRACT: FNOL3 is a Fortran IV subprogram which uses fourth order Runge-Kutta and Adams-Moulton methods to solve up to 30 ordinary differential equations with initial conditions. Options allow control of error, step-size, print frequency and integration method. There is a discussion on the integration methods and their error terms. Listings of the subprogram and sample problems and their results as run on NOL's CDC 6400 are included.

U.S. NAVAL ORDNANCE LABORATORY  
WHITE OAK, MARYLAND

NOLTR 71-2

1 March 1971

FNOL3, A Computer Program to Solve Ordinary Differential Equations

This report describes a computer program to solve ordinary differential equations which may originate in any of the engineering sciences. It is part of a library of programs available to all users of NOL's CDC 6400 computer.

GEORGE G. BALL  
Captain, USN  
Commander



E. K. RITTER  
By direction

## CONTENTS


	Page
I. INTRODUCTION .....	1
II. DESCRIPTION OF THE METHODS .....	1
III. THE ERROR TERMS .....	2
IV. AUTOMATIC ADJUSTMENT OF STEP SIZE .....	5
V. PROGRAMMING .....	7
VI. EXAMPLES .....	12
VII. REMARKS .....	16
VIII. ACKNOWLEDGMENT .....	17
APPENDIX A .....	A-1
Listing of Example No. 1 with Control Cards for the NOLOS System used at NOL	
APPENDIX B .....	B-1
Listing of Example No. 2	
APPENDIX C .....	C-1
Listing of Example No. 3	
APPENDIX D .....	D-1
Listing of FNOL3	
APPENDIX E .....	E-1
FNOL3 vs. FNOL2	
APPENDIX F .....	F-1
FNOL3 Argument List Summary	

## TABLES

Table	Title	Page
1	Results of Example No. 1	18
2	Results of Example No. 2	21
3	Results of Example No. 3	23

## REFERENCES

- (a) Linnekin, J.S. and Belliveau, L.J., FNOL2, A FORTRAN (IBM 7090) Subroutine for the Solution of Ordinary Differential Equations with Automatic Adjustment of the Interval of Integration, NOLTR 63-171, 17 Jul 1963
- (b) Hildebrand, F.B., Introduction to Numerical Analysis, McGraw-Hill Book Company, Inc., 1956



FNOL3, A COMPUTER PROGRAM  
TO SOLVE ORDINARY DIFFERENTIAL EQUATIONS

## I. INTRODUCTION

This report describes a computer program FNOL3 for the numerical integration of ordinary differential equations with initial conditions. These equations are reduced by the user to a system of first order, simultaneous, ordinary differential equations with initial conditions and are solved by using fourth order Runge-Kutta and fourth order Adams-Moulton predictor-corrector methods. FNOL3 is the successor to the Naval Ordnance Laboratory ordinary differential equation solver FNOL2 and uses many features familiar to users of FNOL2 (the differences are provided in Appendix E). See reference (a).

FNOL3 is formulated so as to be quite separate from any particular application. Options make available a convenient flexible package that can be used whenever the problem is expressible as a system of equations as described above.

The program is written in the FORTRAN IV language for the operating system currently used on the Laboratory's CDC 6400 computer.

## II. DESCRIPTION OF THE METHODS

The discussions that follow in this section and in Section III are taken from reference (b). The notation used omits commas from subscripts ( $f_{in}$ ) except when there might be an ambiguity ( $f_{i,n+1}$ ).  $Y$  is used for true values of the dependent variable and  $y$  for computed values.

Let the system of equations to be solved be given in the form:

$$y'_i = \frac{dy_i}{dx} = f_i(x, y_1, y_2, \dots, y_N) \quad i = 1, 2, \dots, N \quad (1a)$$

$$y_i(x_0) = y_{i0} \quad i = 1, 2, \dots, N \quad (1b)$$

$$T = T(x, y_1, y_2, \dots, y_N, y'_1, y'_2, \dots, y'_N) = 0 \quad (1c)$$

where  $T$  is the termination condition and  $y_{10}, y_{20}, \dots, y_{N0}$  are the initial conditions at  $x = x_0$ .

Let  $y_{in}$  be the value of  $y_i$  and  $f_{in}$  be the value of  $f_i$  at  $x=x_n$ . Let  $h$  be the step size in the independent variable  $x$ . The Runge-Kutta method uses the following formulae with the appropriate initial conditions to go from step  $n$  to step  $n+1$ .

$$k_{11} = f_i(x_n, y_{1n}, \dots, y_{Nn}) \quad i = 1, 2, \dots, N \quad (2a)$$

$$k_{12} = f_i(x_n + \frac{1}{2}h, y_{1n} + \frac{1}{2}hk_{11}, \dots, y_{Nn} + \frac{1}{2}hk_{N1}) \quad i = 1, 2, \dots, N \quad (2b)$$

$$k_{13} = f_i(x_n + \frac{1}{2}h, y_{1n} + \frac{1}{2}hk_{12}, \dots, y_{Nn} + \frac{1}{2}hk_{N2}) \quad i = 1, 2, \dots, N \quad (2c)$$

$$k_{14} = f_i(x_n + h, y_{1n} + hk_{13}, \dots, y_{Nn} + hk_{N3}) \quad i = 1, 2, \dots, N \quad (2d)$$

$$y_{i,n+1} = y_{in} + \frac{h}{6}(k_{11} + 2k_{12} + 2k_{13} + k_{14}) \quad i = 1, 2, \dots, N \quad (2e)$$

The Adams-Moulton predictor-corrector method uses the following formulae to compute the values of  $y_{i,n+1}$  using the values of  $y_{i,n-3}$ ,  $y_{i,n-2}$ ,  $y_{i,n-1}$ , and  $y_{in}$ .

$$y_{i,n+1}^{(p)} = y_{in} + \frac{h}{24}(55f_{in} - 59f_{i,n-1} + 37f_{i,n-2} - 9f_{i,n-3}) \quad i = 1, 2, \dots, N \quad (3a)$$

$$y_{i,n+1}^{(c)} = y_{in} + \frac{h}{24}(9f_{i,n+1}^{(p)} + 19f_{in} - 5f_{i,n-1} + f_{i,n-2}) \quad i = 1, 2, \dots, N \quad (3b)$$

where the values of  $y_i$  at  $x_1$ ,  $x_2$ , and  $x_3$  are found by using the Runge-Kutta formulae.  $x_4$  is the first point at which the Adams-Moulton method is used.

Observe that the Adams-Moulton formulae only require two derivative evaluations to go to the next step. The Runge-Kutta method requires four derivative evaluations for each step.

### III. THE ERROR TERMS

We will assume in this section only one ordinary differential equation, so the  $i$  from  $y_{in}$  and  $f_{in}$  is omitted. The error term for the Adams-Moulton method is as follows:



$$y_{n+1}^{(p)} = y_n + \frac{h}{24} (55f_n - 59f_{n-1} + 37f_{n-2} - 9f_{n-3}) \quad (1a)$$

$$y_{n+1}^{(c)} = y_n + \frac{h}{24} (9f_{n+1}^{(p)} + 19f_n - 5f_{n-1} + f_{n-2}) \quad (1b)$$

where  $p$  stands for predicted value and  $c$  for corrected value.  $f_{n+1}^{(p)}$  means calculate  $f$  at  $x_{n+1}$  using  $y_{n+1}^{(p)}$ .

If the calculated values of  $y_1, y_2, \dots, y_n$  and accordingly, of  $f_1, f_2, \dots, f_n$  were exactly correct, then the true ordinate at  $x_{n+1}$ , say  $Y_{n+1}$  would satisfy the equations

$$Y_{n+1} = y_n + \frac{h}{24} (55f_n - 59f_{n-1} + 37f_{n-2} - 9f_{n-3}) + \frac{251}{720} h^5 y^{(5)}(\xi_1) \quad (2a)$$

$$Y_{n+1} = y_n + \frac{h}{24} (9f_{n+1} + 19f_n - 5f_{n-1} + f_{n-2}) - \frac{19}{720} h^5 y^{(5)}(\xi_2) \quad (2b)$$

where  $\xi_1$  and  $\xi_2$  both lie between  $x_{n-3}$  and  $x_{n+1}$ .  $y^{(5)}(\xi_1)$  is the fifth derivative of  $y$  at  $x = \xi_1$ . So it follows from (1) and (2) that

$$Y_{n+1} - y_{n+1}^{(p)} = \frac{251}{720} h^5 y^{(5)}(\xi_1) \quad (3a)$$

$$Y_{n+1} - y_{n+1}^{(c)} = \frac{3h}{8} (f_{n+1} - f_{n+1}^{(p)}) - \frac{19}{720} h^5 y^{(5)}(\xi_2) \quad (3b)$$

Let  $F(x_{n+1}, Y_{n+1}) = f_{n+1}(x_{n+1}, Y_{n+1})$ , applying the law of the mean

$$f_{n+1} - f_{n+1}^{(p)} = F(x_{n+1}, Y_{n+1}) - F(x_{n+1}, y_{n+1}^{(p)}) = (Y_{n+1} - y_{n+1}^{(p)}) F_y(x_{n+1}, \eta_{n+1}) \quad (4)$$

where  $\eta_{n+1}$  is between  $Y_{n+1}$  and  $y_{n+1}^{(p)}$ .

It is assumed that  $h$  is sufficiently small to ensure that

$$\frac{3h}{8} |F_y(x_{n+1}, \eta_{n+1})| \ll 1 \quad (5)$$

and also that  $y^{(5)}(x)$  does not vary strongly for  $x_{n-3} < x < x_{n+1}$  so that  $y^{(5)}(\xi_1)$  and  $y^{(5)}(\xi_2)$  can be equated. Equations (3) lead to the useful approximate relation

$$\frac{720}{251} (Y_{n+1} - y_{n+1}^{(p)}) = h^5 y^{(5)}(\xi)$$

$$Y_{n+1} - y_{n+1}^{(c)} = \frac{3h}{8} (Y_{n+1} - y_{n+1}^{(p)}) F_y(x_{n+1}, \eta_{n+1}) - \left(\frac{19}{720}\right) \left(\frac{720}{251}\right) (Y_{n+1} - y_{n+1}^{(p)})$$

$$Y_{n+1} - y_{n+1}^{(c)} = \left(\frac{3h}{8} F_y(x_{n+1}, \eta_{n+1}) - \frac{19}{251}\right) (Y_{n+1} - y_{n+1}^{(p)})$$

so from (5)

$$\begin{aligned} Y_{n+1} - y_{n+1}^{(c)} &\cong -\frac{19}{251}(Y_{n+1} - y_{n+1}^{(p)}) \\ Y_{n+1} + \frac{19}{251} Y_{n+1} &\cong y_{n+1}^{(c)} + \frac{19}{251} y_{n+1}^{(p)} \\ \frac{270}{251} Y_{n+1} &\cong \frac{270}{251} y_{n+1}^{(c)} - \frac{19}{251} y_{n+1}^{(c)} + \frac{19}{251} y_{n+1}^{(p)} \end{aligned}$$

Therefore,

$$Y_{n+1} \cong y_{n+1}^{(c)} + \frac{1}{14} (y_{n+1}^{(p)} - y_{n+1}^{(c)}) \quad (6)$$

This is the equation programmed when the Adams-Moulton method is selected.

The fourth order Runge-Kutta formulae are

$$k_1 = f(x_n, y_n) \quad (7a)$$

$$k_2 = f(x_n + \frac{1}{2}h, y_n + \frac{1}{2}hk_1) \quad (7b)$$

$$k_3 = f(x_n + \frac{1}{2}h, y_n + \frac{1}{2}hk_2) \quad (7c)$$

$$k_4 = f(x_n + h, y_n + hk_3) \quad (7d)$$

$$y_{n+1} = y_n + \frac{h}{6}(k_1 + 2k_2 + 2k_3 + k_4). \quad (7e)$$

No simple expressions are known for the precise truncation errors in the preceding formulae. An estimate of the error can be obtained, in practice, in the following way. Let the truncation error associated with a formula of 4th-order accuracy in advancing from  $x_n$  to that at  $x_{n+1} = x_n + h$  in a single step be denoted by  $c_n h^5$ . Also suppose that  $c_n$  varies "slowly" with  $n$  and is nearly independent of  $h$  when  $h$  is small. Then if the true value of  $y$  at  $x_{n+1}$  is denoted by  $Y_{n+1}$ , the value obtained by two steps starting at  $x_{n-1}$  by  $y_{n+1}^{(h)}$ , and the value obtained by a single step with doubled spacing  $2h$  by  $y_{n+1}^{(2h)}$ , there follows approximately

$$Y_{n+1} - y_{n+1}^{(h)} \cong 2c_n h^5 \quad (8a)$$

$$Y_{n+1} - y_{n+1}^{(2h)} \cong c_n (2h)^5 \quad (8b)$$

when  $h$  is small.

From equation (8b)

$$Y_{n+1} - y_{n+1}^{(2h)} \cong 2^5 c_n h^5$$

so

$$Y_{n+1} - y_{n+1}^{(2h)} \cong 2^4 (Y_{n+1} - y_{n+1}^{(h)})$$

Therefore,

$$Y_{n+1} \cong y_{n+1}^{(h)} + \frac{y_{n+1}^{(h)} - y_{n+1}^{(2h)}}{15} \quad (9)$$

This is the equation programmed when the Runge-Kutta method is selected.

#### IV. AUTOMATIC ADJUSTMENT OF STEP SIZE

FNOL3 has the option of automatically varying the step size  $h$ , to hold the truncation errors within bounds fixed by the user. The absolute truncation errors for the Adams-Moulton method from III-6 are

$$AE_i = \frac{y_{i,n+1}^{(p)} - y_{i,n+1}^{(c)}}{14} \quad i = 1, 2, \dots, N \quad (1)$$

and the relative truncation errors are

$$RE_i = \frac{AE_i}{y_{i,n+1}^{(c)}} \quad i = 1, 2, \dots, N \quad (2)$$

The absolute truncation errors for the Runge-Kutta method from III-9 are

$$AE_i = \frac{y_{i,n+1}^{(h)} - y_{i,n+1}^{(2h)}}{15} \quad i = 1, 2, \dots, N \quad (3)$$

and the relative truncation errors are

$$RE_i = \frac{AE_i}{y_{i,n+1}^{(h)}} \quad i = 1, 2, \dots, N \quad (4)$$

To determine the step size at each step, let  $E_1, E_2, \dots, E_N$  be the errors whether they are absolute or relative errors and let XNE be a step size control parameter (see page 8). Then if  $10^{-XNE-3} \leq |E_i| \leq 10^{-XNE}$  for  $i = 1, 2, \dots, N$ , the step size is not changed. But if  $|E_i| \leq 10^{-XNE-3}$  for all  $i$ , then let

$$HB = \text{minimum}_i \frac{10^{-XNE-1.5}}{|E_i| + 10^{-11}} > 1 \quad (5)$$

and the step size is increased to  $HB^{1/5} \cdot h$ . If  $|E_j| > 10^{-XNE}$  for some  $j$  then

$$HB = \text{minimum}_j \frac{10^{-XNE-1.5}}{|E_j| + 10^{-11}} < 1 \quad (6)$$

and the step size is decreased to  $HB^{1/5} \cdot h$ .

V. PROGRAMMING

The user must write a calling program hereafter called MAIN, and three auxiliary subprograms. The latter are usually called DERIV, TERM, and OUTPUT and are described later in this section. Besides calling on FNOL3 and providing it with initial values, MAIN must contain an EXTERNAL card which denotes that DERIV, TERM and OUTPUT are the names of subprograms, not variables.

The calling sequence for FNOL3 is

```
EXTERNAL DERIV, TERM, OUTPUT
CALL FNOL3 (J,N,G,L,M,XNE,X,Y,D,DERIV,TERM,OUTPUT)
```

J: (INPUT,INTEGER)

This parameter indicates the integration method.

J = 1 Use Runge-Kutta method of integration to termination. Truncation errors are not calculated; the step size G is not adjustable.

J = 2 Use Runge-Kutta for the first three steps, then Adams-Moulton for the remainder of the interval of integration. Truncation errors are calculated. The step size is adjustable unless XNE = 0. If the step size is adjusted, new starting values are obtained through the Runge-Kutta method.

J = 3 Use Runge-Kutta throughout. The truncation errors are calculated; the step size is adjustable unless XNE = 0.

N: (INPUT,INTEGER)

This is the number of simultaneous first order differential equations to be solved. The maximum number of equations is 30.

G: (INPUT,REAL)

This is the initial step size; upon return from FNOL3, G retains its original value.

L: (INPUT,INTEGER)

This is the number of Y's beyond (N+3) to be written in the routine OUTPUT. These additional Y's should be calculated in the routine TERM, beginning with Y(N+3+1) to Y(N+3+L).

M: (INPUT,INTEGER)

This is the number of accepted steps taken between calls to routine OUTPUT. If  $M = 0$ , then printing is determined by values assigned to Y(N+1) and Y(N+2).  $Y(N+1) = f(X, Y(1), \dots, Y(N), D(1), \dots, D(N))$  and is defined in routine TERM. To generate a call to OUTPUT, Y(N+1) must change by an amount greater than Y(N+2) since the last call to OUTPUT. Y(N+2) is assigned a constant value in the routine which calls FNOL3.

XNE: (INPUT,REAL)

This is the step size control. The step size is unchanged if the worst of all the errors lies within the window  $[10^{-XNE-3}, 10^{-XNE}]$ . The step size is increased if the errors are all less than  $10^{-XNE-3}$ . The step size is decreased if for some differential equation the error is greater than  $10^{-XNE}$ .

If  $Y(N+3) < 0$ . and  $XNE \neq 0$ ., the automatic adjustment of the step size is a function of the absolute errors.

If  $Y(N+3) = 0$ . and  $XNE \neq 0$ ., the automatic adjustment of the step size is a function of the relative errors.

If  $Y(N+3) = \epsilon > 0$ . and  $XNE \neq 0$ ., the automatic adjustment of the step size is a function of the relative errors where the relative errors are equal to the absolute errors divided by the maximum  $(Y(N+3), |Y(I)|)$ . This option removes the possibility of using "small" functional values to compute relative error, otherwise this option is identical to the previous option and is to be preferred over it.

If  $XNE = 0.$ , the step size  $G$  is not adjustable.

X: (INPUT,OUTPUT,REAL)

This is the independent variable. An initial value must be specified before calling FNOL3. FNOL3 will return with  $X$ , the terminal value of the independent variable.

Y: (INPUT,OUTPUT,REAL)

This is the name given the solution array.  $Y$  must be dimensioned at least  $Y(N+3+L)$ . Initial values for  $Y(1), Y(2), \dots, Y(N)$  must be specified before calling FNOL3. If  $L > 0$ , then  $Y(N+3+1), \dots, Y(N+3+L)$  may be used to calculate additional values in the routine TERM. Upon returning from FNOL3,  $Y(1), \dots, Y(N), Y(N+3+1), \dots, Y(N+3+L)$  have the values computed at the terminal value of  $X$ .

D: (OUTPUT,REAL)

This is the name given to the array where the derivatives are stored and must be defined in routine DERIV.  $D$  should be dimensioned  $D(N)$ . Upon returning from FNOL3,  $D(1), \dots, D(N)$  have the values computed at the terminal value of  $X$ .

DERIV:

In this routine the user must compute the  $N$  derivatives. The general form is

```
SUBROUTINE DERIV (X,Y,D)
DIMENSION Y(1),D(1)
D(1) = ...
D(2) = ...
:
D(N) = ...
RETURN
END
```

No D beyond D(N) should be calculated. If desired, additional data may be passed between this routine and the other user written routines via COMMON statements.

#### TERM:

The user evaluates the termination criterion ( $T = T(X, Y(1), \dots, Y(N), D(1), \dots, D(N))$ ) in this routine. Auxiliary values such as  $Y(N+1)$  and those required for plotting purposes should be calculated here because this routine is entered only once per accepted step before termination.

A termination loop of at most four iterations starts when T undergoes a change of sign. After the very first step of the integration, termination may occur without looping when  $|T| \leq 10^{-6}$ .

The general form is

```
SUBROUTINE TERM (X,Y,D,T)
DIMENSION Y(1),D(1)
T = ...
RETURN
END
```

#### OUTPUT:

This user routine is entered at the beginning and end of the complete integration. If  $M \neq 0$ , it is entered every Mth accepted step. If  $M = 0$  then  $Y(N+1)$  and  $Y(N+2)$ , discussed under parameter M determine the print frequency.

The general form is

```
SUBROUTINE OUTPUT (X,Y,D,ERROR,N,L,H)
DIMENSION Y(1),D(1),ERROR(1)
:
:
PRINT ...
:
RETURN
END
```

X, Y, D, N, and L are the same as in the calling sequence of FNOL3.

ERROR is the name given the array which contains the absolute errors.



H is the step size used to get to the present step. If the magnitude of a new step size becomes less than  $H_1 = 10^{-6} * |x| + 10^{-11}$ , then two steps are taken using the Runge-Kutta method with step size equal to  $H_1$  or  $-H_1$  depending on the direction of integration. If the errors are too large, the two steps will be accepted and two more steps are taken using the Runge-Kutta method with a step size computed in the same way as above using the current x. If the errors are still too large after the above procedure is done ten times, then an error message is written and the program stops after going to OUTPUT. If at any step the errors are not too large, then FNOL3 continues in the normal manner after resetting the counter back to zero.

VI. EXAMPLES

The examples section of this report contains three problems which illustrate the available options of FNOL3.

Example No. 1

Solve the first order linear differential equation

$$\frac{dy}{dx} = \omega A \cos(\omega x)$$

in the interval  $[0, 3\pi]$  for the initial condition

$$y(0) = 0$$

Choose the case  $\omega = A = 1$ .

Use the three available methods of FNOL3 to numerically integrate the given differential equation over  $[0, 3\pi]$ .

(I) Use the fourth order Runge-Kutta method with a constant step size of .1.

(II) Use the fourth order Adams-Moulton predictor-corrector formulae with an adjustable step size to hold the relative truncation error in the window  $[10^{-8}, 10^{-5}]$ .

(III) Use the fourth order Runge-Kutta method with an adjustable step size to hold the relative truncation error in the window  $[10^{-8}, 10^{-5}]$ .

The analytic solution of the given equation with respect to the given initial condition is

$$y(x) = A \sin(\omega x).$$

The actual value of  $\sin(x)$  is computed for each  $x$  and compared to the calculated value of the solution. At every fifth accepted step, the solution,  $\sin(x)$ , and

the difference of the actual and calculated solutions are printed. These results are in Table 1.

The main (calling) program and the necessary subroutines to accomplish the solution of the stated problem in the manner indicated are in Appendix A.

### Example No. 2

Solve the second order linear differential equation

$$\frac{d^2 y}{dx^2} = -y$$

in the interval  $[0, 5\pi]$  for the initial conditions

$$y(0) = 0$$

$$y'(0) = 1$$

Reduce the second order linear differential equation to a system of two first order equations

$$\frac{dy_1}{dx} = y_2$$

$$\frac{dy_2}{dx} = -y_1$$

with the initial conditions

$$y_1(0) = 0$$

$$y_2(0) = 1$$

Use the Adams-Moulton predictor-corrector method to integrate the given differential equations over  $[0, 5\pi]$ . An adjustable step size is used with size determined by

(I) Relative truncation error

(II) Absolute truncation error

The error window is  $[10^{-8}, 10^{-5}]$ .

Two types of printing options are illustrated in this example

(I) Printing every kth step (10 in this example)

(II) Printing when the independent variable has changed by a pre-selected amount (1 in this example)

The analytic solution of the given equation with respect to the given initial conditions is

$$y(x) = \sin(x)$$

The actual value of  $\sin(x)$  is computed for each  $x$  and compared to the calculated value of the solution. At every print cycle the solution,  $\sin(x)$ , and the difference of the actual and calculated solutions are printed. These results are in Table 2.

The main (calling) program and the necessary subroutines to accomplish the solution of the stated problem in the manner indicated are in Appendix B.

### Example No. 3

Solve the system of first order linear differential equations

$$\frac{dy_1}{dx} = y_2 \tag{1}$$

$$\frac{dy_2}{dx} = -y_1 \tag{2}$$

$$\frac{dy_3}{dx} = \left( \frac{1}{x+1} - 1 \right) y_3 \tag{3}$$

$$\frac{dy_4}{dx} = y_4 - x+1 \tag{4}$$

$$\frac{dy_5}{dx} = \frac{1}{x+1} \tag{5}$$

in the interval  $[0, 5\pi]$  for the initial conditions

$$y_1(0) = 0$$

$$y_2(0) = 1$$

$$y_3(0) = 1$$

$$y_4(0) = 1$$

$$y_5(0) = 0$$

Use the Adams-Moulton predictor-corrector method to integrate the given system of differential equations over  $[0, 5\pi]$ . An adjustable step size is used with size adjusted to hold the relative truncation error in the window  $[10^{-8}, 10^{-5}]$ .

Printing occurs every 40 accepted steps. The analytic solutions of the given equations with respect to the given initial conditions are

$$y_1(x) = \sin(x)$$

$$y_2(x) = \cos(x)$$

$$y_3(x) = (x+1)e^{-x}$$

$$y_4(x) = x + e^x$$

$$y_5(x) = \log_e(x+1)$$

The actual values of the solutions are computed at each  $x$  and compared to the calculated values of the solutions. At each print cycle the actual solutions, calculated solutions, and differences are printed. These results are in Table 3.

The main (calling) program and the necessary subroutines to accomplish the solution of the stated problem in the manner indicated are in Appendix C.

VII. REMARKS

Some suggestions and warnings are in order based on the years of experience with previous versions of this routine. This version of FNOL3 is a conversion from the IBM 7090, and what was one auxiliary routine with multiple entries has been changed to three auxiliary routines. In addition, double precision has been deemed unnecessary due to the increased precision of the CDC 6400.

J: Adams-Moulton is the prime method of this routine, but Runge-Kutta is needed to start, and whenever the time step changes. Adams-Moulton requires only 2 entries into DERIV per time step while Runge-Kutta requires 4.

L: This parameter is a hangover from previous versions of FNOL3 in which the user did not write an OUTPUT routine but simply specified how many (L) auxiliary values were to be printed.

M: FNOL3 always prints initial and final values even if M has been set to some very large value. However, some output is always needed to shed light on how the integration has proceeded.

Printing at specified intervals cannot be insured except by fixed timesteps or terminating and then printing. Setting  $M = 0$  and  $Y(N+2)=DELTAY$  in MAIN and  $Y(N+1)=Y(1)$  in TERM, only causes no printing until  $Y(1)$  changes by at least  $Y(N+2)$ . To force printing at exact intervals of  $Y(N+2)$  in  $Y(1)$ , put FNOL3 in a loop in MAIN and in TERM set  $T=Y(1)-C$ . In MAIN set  $C=Y(1)+Y(N+2)$  before calling FNOL3.  $C$  may be transmitted via the  $Y$  array or through COMMON. The final value of  $Y(1)$  of each integration becomes the initial value for the next integration.

Y: Unless COMMON is used, additional parameters necessary for computation should be sent from routine to routine through the  $Y$  array in locations starting with  $Y(N+4)$ . If  $M \neq 0$  then  $Y(N+1)$  and  $Y(N+2)$  are available

to the programmer. If  $XNE = 0$  then  $Y(N+3)$  is available. In other cases these three locations have special meaning. See the discussions on  $M$  and  $XNE$  above and in Section V.

D: We repeat here for emphasis. DO NOT USE a  $D$  beyond  $D(N)$ ! In all we have said, there is an assumption that the derivatives can be computed explicitly from  $X$  and the current  $Y$  values. If this is not so, the alternative is to perform root-finding within  $DERIV$ . If the routine that calls  $FNOL3$  initializes the  $D$  array, these values will be available in  $DERIV$ . However, unless they are saved in another array, each time  $DERIV$  is entered, the previous  $D$ 's are lost.

ERROR: At the start of an integration or whenever the step size changes, the absolute truncation errors are not computed directly for the first step. Runge-Kutta is called at that time, and its error term requires having  $y_{i,n+1}^{(h)}$  and  $y_{i,n+1}^{(2h)}$ , see equation IV-3. The first term,  $y_{i,n+1}^{(h)}$ , means reaching  $x_{n+1}$  by taking two steps of size  $h$ , while the second term,  $y_{i,n+1}^{(2h)}$ , means reaching  $x_{n+1}$  by taking one step of size  $2h$ . It is only after these three steps are taken that an error term can be computed. Accepting or rejecting the first step is based on this error, which is then treated as if it were the first error. At least three Runge-Kutta steps of size  $h$  are taken before Adams-Moulton takes over.

#### VIII. ACKNOWLEDGMENT

NOL has had an ordinary differential equations solver since 1959, and  $FNOL3$  is the current version. We offer our sincere thanks to L. Hieb, M. Vander Vorst and J. Lyles who helped to checkout and criticise the  $FNOL3$  program and writeup. A number of improvements were made on the basis of their suggestions. Mrs. G. Dabbs then did a commendable job of typing the document.

TABLE 1

$$\frac{dy}{dx} = \omega A \cos(\omega x)$$

x	<u>Method (I)</u>		(YT-YC)
	YT=TRUE sin(x)	YC=COMPUTED sin(x)	
0.0	0.0	0.0	0.0
0.5	.479426	.479426	-17x10 <sup>-9</sup>
1.0	.841471	.841471	-29x10 <sup>-9</sup>
1.5	.997495	.997495	-35x10 <sup>-9</sup>
2.0	.909297	.909297	-32x10 <sup>-9</sup>
2.5	.598472	.598472	-21x10 <sup>-9</sup>
3.0	.141120	.141120	-49x10 <sup>-10</sup>
3.5	-.350783	-.350783	12x10 <sup>-9</sup>
4.0	-.756802	-.756803	26x10 <sup>-9</sup>
4.5	-.977530	-.977530	34x10 <sup>-9</sup>
5.0	-.958924	-.958924	33x10 <sup>-9</sup>
5.5	-.705540	-.705540	25x10 <sup>-9</sup>
6.0	-.279415	-.279416	97x10 <sup>-10</sup>
6.5	.215120	.215120	-75x10 <sup>-10</sup>
7.0	.656987	.656987	-23x10 <sup>-9</sup>
7.5	.938000	.938000	-33x10 <sup>-9</sup>
8.0	.989358	.989358	-34x10 <sup>-9</sup>
8.5	.798487	.798487	-28x10 <sup>-9</sup>
9.0	.412118	.412118	-14x10 <sup>-9</sup>
9.424778	-39x10 <sup>-9</sup>	-41x10 <sup>-9</sup>	17x10 <sup>-10</sup>



TABLE 1

$$\frac{dy}{dx} = \omega A \cos(\omega x)$$

x	Method (II)		
	YT=TRUE sin(x)	YC=COMPUTED sin(x)	(YT-YC)
0.0	0.0	0.0	0.0
0.5	.479426	.479426	22x10 <sup>-9</sup>
1.0	.841471	.841471	92x10 <sup>-9</sup>
1.5	.997495	.997495	18x10 <sup>-8</sup>
2.216974	.798391	.798391	24x10 <sup>-8</sup>
2.822212	.313979	.313979	16x10 <sup>-8</sup>
3.219365	-.0776944	-.0776946	17x10 <sup>-8</sup>
3.729709	-.554795	-.554795	13x10 <sup>-8</sup>
4.240053	-.890508	-.890508	47x10 <sup>-9</sup>
4.750397	-.999278	-.999278	-59x10 <sup>-9</sup>
5.260741	-.853385	-.853384	-16x10 <sup>-8</sup>
5.771085	-.490009	-.490009	-23x10 <sup>-8</sup>
6.220706	-.0624391	-.0624388	-25x10 <sup>-8</sup>
6.658950	.366984	.366985	-24x10 <sup>-8</sup>
7.155075	.765546	.765546	-18x10 <sup>-8</sup>
7.651199	.979510	.979510	-92x10 <sup>-9</sup>
8.353455	.877835	.877835	29x10 <sup>-8</sup>
9.288410	.135945	.135946	-61x10 <sup>-8</sup>
9.424778	-39x10 <sup>-9</sup>	62x10 <sup>-8</sup>	-66x10 <sup>-8</sup>

TABLE 1

$$\frac{dy}{dx} = \omega A \cos(\omega x)$$

Method (III)

x	YT=TRUE sin(x)	YC=COMPUTED sin(x)	(YT-YC)
0.0	0.0	0.0	0.0
0.5	.479426	.479426	12x10 <sup>-9</sup>
1.303726	.964548	.964548	91x10 <sup>-9</sup>
2.309936	.739048	.739048	77x10 <sup>-9</sup>
3.316146	-.173668	-.173668	-46x10 <sup>-8</sup>
4.322356	-.924896	-.924895	-10x10 <sup>-7</sup>
5.297378	-.833718	-.833717	-11x10 <sup>-7</sup>
6.225618	-.0575354	-.0575345	-83x10 <sup>-8</sup>
7.153858	.764763	.764763	-41x10 <sup>-8</sup>
8.082099	.974094	.974094	-23x10 <sup>-8</sup>
9.102580	.316653	.316653	-51x10 <sup>-8</sup>
9.424778	-39x10 <sup>-9</sup>	74x10 <sup>-8</sup>	-78x10 <sup>-8</sup>

TABLE 2

$$\frac{d^2 y}{dx^2} = -y$$

Relative Truncation Error

x	YC=COMPUTED sin(x)	YT=TRUE sin(x)	(YT-YC)
0.0	0.0	0.0	0.0
0.381345	.372169	.372169	27x10 <sup>-9</sup>
1.194792	.930140	.930139	-22x10 <sup>-8</sup>
2.008240	.905838	.905838	-52x10 <sup>-8</sup>
2.821688	.314477	.314476	-39x10 <sup>-8</sup>
3.322058	-.179488	-.179488	11x10 <sup>-9</sup>
4.055814	-.792088	-.792087	72x10 <sup>-8</sup>
4.710873	-1.00000	-.999999	12x10 <sup>-7</sup>
5.262094	-.852680	-.852679	11x10 <sup>-7</sup>
5.953946	-.323324	-.323324	61x10 <sup>-8</sup>
6.645797	.354718	.354717	-30x10 <sup>-8</sup>
7.337648	.869636	.869635	-12x10 <sup>-7</sup>
8.029500	.984638	.984636	-17x10 <sup>-7</sup>
8.721351	.646836	.646835	-13x10 <sup>-7</sup>
9.413203	.0115755	.0115752	-32x10 <sup>-8</sup>
10.105054	-.629009	-.629008	99x10 <sup>-8</sup>
10.796905	-.980332	-.980330	20x10 <sup>-7</sup>
11.488757	-.880833	-.880831	21x10 <sup>-7</sup>
12.180608	-.376267	-.376266	12x10 <sup>-7</sup>
12.872459	.301332	.301332	-34x10 <sup>-8</sup>
13.564311	.840358	.840356	-19x10 <sup>-7</sup>
14.256162	.992931	.992928	-27x10 <sup>-7</sup>
14.948014	.688887	.688885	-22x10 <sup>-7</sup>
15.639865	.0680464	.0680457	-69x10 <sup>-8</sup>
15.707963	76x10 <sup>-8</sup>	27x10 <sup>-8</sup>	-50x10 <sup>-8</sup>

TABLE 2

$$\frac{d^2 y}{dx^2} = -y$$

Absolute Truncation Error

x	YC=COMPUTED sin(x)	YT=TRUE sin(x)	(YT-YC)
0.0	0.0	0.0	0.0
1.008358	.845958	.845957	-91x10 <sup>-8</sup>
2.030260	.896293	.896290	-30x10 <sup>-7</sup>
3.052163	.0893123	.0893108	-16x10 <sup>-7</sup>
4.074065	-.803100	-.803096	46x10 <sup>-7</sup>
5.095968	-.927340	-.927331	89x10 <sup>-7</sup>
6.117870	-.164568	-.164563	43x10 <sup>-7</sup>
7.139773	.755619	.755612	-75x10 <sup>-7</sup>
8.161675	.953050	.953035	-15x10 <sup>-6</sup>
9.183578	.238876	.238868	-79x10 <sup>-7</sup>
10.205480	-.703788	-.703778	96x10 <sup>-7</sup>
11.227383	-.973273	-.973253	21x10 <sup>-6</sup>
12.249285	-.311811	-.311799	12x10 <sup>-6</sup>
13.271187	.647905	.647894	-11x10 <sup>-6</sup>
14.293090	.987895	.987869	-27x10 <sup>-6</sup>
15.314992	.382952	.382935	-17x10 <sup>-6</sup>
15.707963	76x10 <sup>-7</sup>	27x10 <sup>-8</sup>	-74x10 <sup>-7</sup>

TABLE 3

x	EQUATION NO.	YC=COMPUTED y	YT=TRUE y	(YT-YC)
0.0	1	0.0	0.0	0.0
	2	1.0	1.0	0.0
	3	1.0	1.0	0.0
	4	1.0	1.0	0.0
	5	0.0	0.0	0.0
2.3055	1	.742059	.742058	$-13 \times 10^{-8}$
	2	-.670335	-.670335	$91 \times 10^{-9}$
	3	.329598	.329598	$-20 \times 10^{-9}$
	4	12.3342	12.3342	$15 \times 10^{-7}$
	5	1.19557	1.19557	$19 \times 10^{-8}$
4.6901	1	-.999753	-.999753	$34 \times 10^{-8}$
	2	-.0222392	-.0222391	$63 \times 10^{-9}$
	3	-.0522659	-.0522659	$-37 \times 10^{-10}$
	4	113.559	113.559	$35 \times 10^{-6}$
	5	1.73874	1.73874	$20 \times 10^{-8}$
7.0748	1	.711517	.711516	$-31 \times 10^{-8}$
	2	.702670	.702669	$-43 \times 10^{-8}$
	3	.00683235	.00683235	$-18 \times 10^{-11}$
	4	1188.93	1188.93	$59 \times 10^{-5}$
	5	2.08875	2.08875	$20 \times 10^{-8}$

TABLE 3

x	EQUATION NO.	YC=COMPUTED y	YT=TRUE y	(YT-YC)
9.4595	1	-.0347456	-.0347457	$-98 \times 10^{-9}$
	2	-.999397	-.999396	$71 \times 10^{-8}$
	3	$.815249 \times 10^{-3}$	$.815249 \times 10^{-3}$	$43 \times 10^{-12}$
	4	12839.3	12839.3	$86 \times 10^{-4}$
	5	2.34751	2.34751	$20 \times 10^{-8}$
11.8442	1	-.660999	-.660999	$70 \times 10^{-8}$
	2	.750388	.750387	$-56 \times 10^{-8}$
	3	$.922205 \times 10^{-4}$	$.922205 \times 10^{-4}$	$14 \times 10^{-12}$
	4	139289.	139289.	$12 \times 10^{-2}$
	5	2.55289	2.55289	$20 \times 10^{-8}$
14.2289	1	.995795	.995794	$-11 \times 10^{-7}$
	2	-.0916176	-.0916177	$-90 \times 10^{-9}$
	3	$.100723 \times 10^{-4}$	$.100723 \times 10^{-4}$	$27 \times 10^{-13}$
	4	$.151197 \times 10^7$	$.151197 \times 10^7$	$15 \times 10^{-1}$
	5	2.72320	2.72320	$20 \times 10^{-8}$
15.7080	1	$.797718 \times 10^{-6}$	$.587949 \times 10^{-6}$	$-21 \times 10^{-8}$
	2	-1.00000	-1.00000	$12 \times 10^{-7}$
	3	$.251792 \times 10^{-5}$	$.251792 \times 10^{-5}$	$87 \times 10^{-14}$
	4	$.663563 \times 10^7$	$.663564 \times 10^7$	$75 \times 10^{-1}$
	5	2.81589	2.81589	$20 \times 10^{-8}$

APPENDIX A  
LISTING OF EXAMPLE NO. 1 WITH CONTROL CARDS  
FOR THE NOLOS SYSTEM USED AT NOL

```

CCAFNOL,T100,CM60000.SYSTEM,039,ORLOW.
ATTACH(ABC,NOLBIN)
COPYN(0,DEF,ABC)      FIRST PARAMETER IS THE NUMBER '0'
RETURN(ABC)
FTN(L)
LOAD(LGO)
DEF.
'      RECORD SEPARATOR = (7-8-9) PUNCH IN COL. 1
REWIND(ABC)
FNOL3,1,ABC
'      RECORD SEPARATOR = (7-8-9) PUNCH IN COL. 1
      PROGRAM EX1 (INPUT,OUTPUT)

C
C      EXAMPLE NO. 1
C      SOLVE THE INITIAL VALUE PROBLEM  $dy/dx = A * w * \cos(w * x)$ 
C      USING THE FOLLOWING METHODS
C
C      (I)   4TH ORDER RUNGE-KUTTA (CONSTANT STEP)
C      (II)  4TH ORDER ADAMS-MOULTON METHOD (VARIABLE STEP)
C      (III) 4TH ORDER RUNGE-KUTTA (VARIABLE STEP)
C
      DIMENSION Y(20),D(20)
      EXTERNAL DERIV,TERM,OUTPUT
      COMMON A,W
      A=1.
      W=1.
      DO 200 J=1,3
C      NUMBER OF EQUATIONS
      N=1
C      INITIAL STEP SIZE
      G=.1
C      NUMBER OF EXTRA Y'S
      L=2
C      NUMBER OF ACCEPTED STEPS TAKEN BETWEEN PRINTS
      M=5
C      ERROR WINDOW EXPONENT
      XNE=5.
      Y(1)=0.
      Y(N+3)=.01
      X=0.
      PRINT 1000
1000 FORMAT (1H1,4X,1HX,17X,9HYT=TRUE Y,12X,13HYC=COMPUTED Y,11X,
1      10H (YT-YC))
      CALL FNOL3 (J,N,G,L,M,XNE,X,Y,D,DERIV,TERM,OUTPUT)
200 CONTINUE
      STOP
      FND

```

NOLTR 71-2

APPENDIX A CONTINUED

```

SUBROUTINE DERIV (X,Y,D)
DIMENSION D(1)
COMMON A,W
D(1)=A*W*COS(W*X)
RETURN
END
SUBROUTINE TERM (X,Y,D,T)
DIMENSION Y(1)
COMMON A,W
T=X-9.424778
Y(5)=A*SIN(W*X)
Y(6)=Y(5)-Y(1)
RETURN
END
SUBROUTINE OUTPUT (X,Y,D,ERROR,N,L,H)
DIMENSION Y(1)
PRINT 1000, X,Y(5),Y(1),Y(6)
1000 FORMAT (1H ,F10.6,10X,3(E13.6,10X))
RETURN
END
ORLOW 039 CCAFNOL END OF FILE = (6-7-8-9) PUNCH IN COL. 1

```



APPENDIX B  
LISTING OF EXAMPLE NO. 2

```

PROGRAM EX2(INPUT,OUTPUT)
C   EXAMPLE NO. 2
C
C   SOLVE D**2Y/DX**2=-Y
C
C   USING ADAMS-MOULTON PREDICTOR CORRECTOR WITH
C   STEP SIZE CONTROLLED BY
C
C   (I)   RELATIVE ERROR
C   (II)  ABSOLUTE ERROR
C
C   DIMENSION Y(30),D(30)
C   EXTERNAL DERIV,TERM,OUTPUT
C   ADAMS-MOULTON METHOD
C   J=2
C   NUMBER OF EQUATIONS
C   N=2
C   MINIMUM RELATIVE ERROR DIVISOR
C   Y(N+3)=.001
C   NUMBER OF EXTRA Y'S
C   L=2
C   NUMBER OF ACCEPTED STEPS BETWEEN PRINT CYCLES
C   M=10
C   EXPONENT ERROR WINDOW
C   XNE=5.
C   INITIAL STEP SIZE
C   G=.01
C   INITIAL CONDITIONS
C   X=0.
C   Y(1)=0.
C   Y(2)=1.
C   PRINT 1000
1000 FORMAT(1H1,4X,1HX,13X,13HYC=COMPUTED Y,16X,9HYT=TRUE Y,11X,
1      10H (YT-YC))
C   CALL FNOL3(J,N,G,L,M,XNE,X,Y,D,DERIV,TERM,OUTPUT)
C   RESET THE PRINTING OPTION
C   M=0
C   Y(N+2)=1.
C   RESET THE INITIAL CONDITIONS
C   X=0.
C   Y(1)=0.
C   Y(2)=1.
C   CHANGE TO ABSOLUTE ERROR
C   Y(N+3)=-Y(N+3)
C   PRINT 1000
C   CALL FNOL3(J,N,G,L,M,XNE,X,Y,D,DERIV,TERM,OUTPUT)
C   STOP
C   END

```

## APPENDIX B CONTINUED

```
SUBROUTINE DERIV(X,Y,D)
DIMENSION Y(1),D(1)
D(1)=Y(2)
D(2)=-Y(1)
RETURN
END
SUBROUTINE TERM(X,Y,D,T)
DIMENSION Y(1)
T=15.707963-X
Y(3)=X
Y(6)=SIN(X)
Y(7)=Y(6)-Y(1)
RETURN
END
SUBROUTINE OUTPUT(X,Y,D,ERROR,N,L,H)
DIMENSION Y(1)
LF=N+4
LL=N+3+L
PRINT 1000, X,Y(1),(Y(I),I=LF,LL)
1000 FORMAT(1H ,F10.6,10X,3(E13.6,10X))
RETURN
END
```

APPENDIX C  
LISTING OF EXAMPLE NO. 3

```

C      PROGRAM EX3(INPUT,OUTPUT)
C      EXAMPLE NO. 3
C
C      SOLVE THE SYSTEM OF FIRST ORDER EQUATIONS
C
C      DY(1)/DX=Y(2)
C      DY(2)/DX=-Y(1)
C      DY(3)/DX=(1./(X+1.)-1.)*Y(3)
C      DY(4)/DX=Y(4)-X+1.
C      DY(5)/DX=1./(X+1.)
C
C      USING ADAMS-MOULTON PREDICTOR CORRECTOR METHOD WITH
C      STEP SIZE CONTROLLED BY RELATIVE ERROR
C
C      DIMENSION Y(30),D(30)
C      EXTERNAL DERIV,TERM,OUTPUT
C      ADAMS-MOULTON METHOD
C      J=2
C      NUMBER OF EQUATIONS
C      N=5
C      MINIMUM RELATIVE ERROR DIVISOR
C      Y(N+3)=.01
C      NUMBER OF EXTRA Y'S
C      L=10
C      NUMBER OF ACCEPTED STEPS BETWEEN PRINT CYCLES
C      M=40
C      EXPONENT ERROR WINDOW
C      XNE=5.
C      INITIAL STEP SIZE
C      G=.02
C      INITIAL CONDITIONS
C      X=0.
C      Y(1)=0.
C      Y(2)=1.
C      Y(3)=1.
C      Y(4)=1.
C      Y(5)=0.
C      PRINT 1000
1000  FORMAT(1H1,4X,1HI,13X,14HYC=COMPUTED YI,14X,10HYT=TRUE YI,11X,
1      10H (YT-YC))
C      CALL FNOL3(J,N,G,L,M,XNE,X,Y,D,DERIV,TERM,OUTPUT)
C      STOP
C      END

```

## APPENDIX C CONTINUED

```
SUBROUTINE DERIV(X,Y,D)
  DIMENSION Y(1),D(1)
  D(1)=Y(2)
  D(2)=-Y(1)
  D(3)=(1./(X+1.)-1.)*Y(3)
  D(4)=Y(4)-X+1.
  D(5)=1./(X+1.)
  RETURN
END
SUBROUTINE TERM(X,Y,D,T)
  DIMENSION Y(1)
  T=X-5.*3.141592536
  Y(9)=SIN(X)
  Y(10)=COS(X)
  Y(11)=(X+1.)*EXP(-X)
  Y(12)=X+EXP(X)
  Y(13)=ALOG(X+1.)
  DO 10 I=14,18
    Y(I)=Y(I-5)-Y(I-13)
10  CONTINUE
  RETURN
END
SUBROUTINE OUTPUT(X,Y,D,ERROR,N,L,H)
  DIMENSION Y(1)
  PRINT 1000, X
1000 FORMAT(1H0,50X,3HX= ,F7.4)
  J=N+3
  K=2*N+3
  DO 20 I=1,N
    J=J+1
    K=K+1
    PRINT 2000, I,Y(I),Y(J),Y(K)
2000 FORMAT(1H ,I5,15X,3(E13.6,10X))
  20  CONTINUE
  RETURN
END
```

APPENDIX D  
LISTING OF FNOL3

```

      SUBROUTINE FNOL3(J,NN,G,L,MPR,XNE,X,Y,D,DERIV,TERM,OUTPUT)
C 001 J=INTEGRATION METHOD CONTROL
C 002 NN=NUMBER OF SIMULTANEOUS DIFFERENTIAL EQUATIONS
C 003 G=FIRST INTERVAL OF INTEGRATION
C 004 L=NUMBER OF Y'S GREATER THAN N TO BE PRINTED
C 005 MPR=PRINT FREQUENCY
C 006 XNE=CONTROL FOR INTERVAL OF INTEGRATION
C 007 X=INDEPENDENT VARIABLE
C 008 Y=DEPENDENT VARIABLE
C 009 D=ARRAY CONTAINING DERIVATIVES
C 010 DERIV=SUBROUTINE IN WHICH DIFFERENTIAL EQUATIONS ARE FOUND
C 011 TERM=SUBROUTINE FOR TERMINATION CONDITION
C 012 OUTPUT=SUBROUTINE FOR PRINTING OUTPUT
C      NRET=TERM LOOP COUNTER
C      NPR=COUNT OF STEPS SINCE LAST PRINT
C      PC=Y(N+1)=PRINT CONTROL OTHER THAN STEP COUNT
C      JJ=J-2=0 FOR AM,-1 FOR RK,+1 FOR RK2
C      MK=AM RK STEP COUNT
C      XD=DP FORM OF X
C THIS SUBROUTINE CAN ALSO BE RUN IN DOUBLE PRECISION BY REMOVING
C THE 'C' IN COLUMN 1 ON THE DOUBLE PRECISION STATEMENT
C      DOUBLE PRECISION XD,YD,YP,YC,YK,H,HC,XS,XDS,HS,HN,HD24,HD6
      DIMENSION C(3),Y(30),YD(30),YP(30),YC(30),D(50),DM(30,4),DK(30,4)
      1,ERROR(30),YK(30)
      DATA EP6,EP11,M4/1.E-6,1.E-11,-4/
      DATA (C(K),K=1,3)/2*.5,1./
      DATA HMAX5/1.F35/
      NHTS=0
      FP2=0.
      N=NN
      JJ=J-2
      H=G
      HN=H
      MK=1
      NRET=M4
      JTEST=1
      IF (JJ.LT. 0) JTEST=4
      IF (XNE.EQ. 0.) GO TO 15
      EC=Y(N+3)
      EUP=10.**(-XNE)
      ELO=EUP*.001
      EM=ELO*31.6227766
15  XD=X
      XS=XD
      DO 20 I=1,N
      ERROR(I)=0.
20  YD(I)=Y(I)
      CALL DERIV(X,Y,D)
      CALL TERM (X,Y,D,F)
C      PRINT

```

NOLTR 71-2  
APPENDIX D CONTINUED

```

50 CALL OUTPUT(X,Y,D,ERROR,N,L,H)
   IF (NRET) 65,60,55
55 PRINT 3000, HN
3000 FORMAT(108H1EXECUTION TERMINATED BECAUSE INTERVAL OF INTEGRATION L
   1ESS THAN 1.0E -6 TIMES INDEPENDENT VARIABLE (X). H =,1PE15.7)
   STOP
60 RETURN
65 NPR=0
   IF (MPR .LE. 0) PC=Y(N+1)
100 IF (JTEST .EQ. 5 .AND. H .NE. HN) GO TO 455
   IF (JJ .GE. 0) H=HN
   IF (MK .NE. 0 .OR. JJ .NE. 0) GO TO 300
C-----THE ADAMS MOULTON METHOD
200 HD24=H/24.
   JAM=0
   DO 210 I=1,N
   YPI=(55.*DM(I,1)+37.*DM(I,2))-(59.*DM(I,3)+9.*DM(I,4))
   YP(I)=YD(I)+HD24*YPI
   Y(I)=YP(I)
210 CONTINUE
   X=XD+H
   CALL DERIV(X,Y,DM(1,4))
   DO 220 I=1,N
   YPI=(9.*DM(I,4)+19.*DM(I,1)+DM(I,2))-5.*DM(I,3)
   YC(I)=YD(I)+HD24*YPI
   ERROR(I)=(YP(I)-YC(I))/14.
C THIS ADDS IN A 2D CORRECTION
   YC(I)=YC(I)+ERROR(I)
220 CONTINUE
   IF (XNE.NE..0) GO TO 700
   GO TO 455
C-----THE RUNGE KUTTA METHOD
300 GO TO (301,309,308,309,303),JTEST
301 DO 302 I=1,N
   YK(I)=YD(I)
302 CONTINUE
   XDS=XD
   GO TO 309
303 DO 304 I=1,N
   YK(I)=YC(I)
304 CONTINUE
   XDS=XD+H
308 HS=H
   H=2.*H
   GO TO 320
309 X=XD
   JAM=1
   DO 310 I=1,N
   Y(I)=YD(I)
   DK(I,1)=D(I)
310 CONTINUE

```

## APPENDIX D CONTINUED

```

      IF (JTEST .LE. 2) CALL DERIV(X,Y,DK)
      IF (MK .GT. 1 .OR. JTEST .GT. 1) GO TO 320
      DO 315 I=1,N
      DM(I,4)=DK(I,1)
315  CONTINUE
320  DO 335 K=2,4
      HC=H*C(K-1)
      DO 330 I=1,N
      Y(I)=YD(I) + HC*DK(I,K-1)
330  CONTINUE
      X=XD+HC
      CALL DERIV(X,Y,DK(1,K))
335  CONTINUE
      HD6=H/6.
      DO 340 I=1,N
      YPI=DK(I,1)+DK(I,4)+2.*(DK(I,2)+DK(I,3))
      YC(I)=YD(I)+HD6*YPI
340  CONTINUE
      GO TO (360,390,370,455,370),JTEST
360  DO 365 I=1,N
      YP(I)=YC(I)
365  CONTINUE
      JTEST=3
      GO TO 308
370  DO 380 I=1,N
      YD(I)=YP(I)
      YP(I)=YC(I)
380  CONTINUE
      H=HS
      XD=XD+H
      JTEST=2
      IF (MK .EQ. 1) GO TO 309
      GO TO 451
390  DO 400 I=1,N
      ERROR(I)=(YC(I)-YP(I))/15.
      YC(I)=YC(I)+ERROR(I)
      YP(I)=YC(I)
400  CONTINUE
      JTEST=5
      IF (XNE.NE..0) GO TO 700
C-----ACCEPT THE STEP SIZE
450  IF (JAM .EQ. 0) GO TO 455
      IF (MK .EQ. 3 .AND. JJ .EQ. 0) GO TO 455
      IF (MK .NE. 1) GO TO 303
      IF (JTEST .EQ. 1) GO TO 455
451  DO 452 I=1,N
      Y(I)=YD(I)
452  CONTINUE
      GO TO 466
455  DO 459 NQ=1,N
      YD(NQ)=YC(NQ)

```

## APPENDIX D CONTINUED

```

      Y(NQ)=YD(NQ)
459  CONTINUE
      IF (JJ .GE. 0) JTEST=1
      IF (MK .NE. 0 .OR. JJ .NE. 0 .OR. NRET .NE. M4) GO TO 465
      DO 460 I=1,N
      DM(I,4)=DM(I,2)
      DM(I,2)=DM(I,3)
      DM(I,3)=DM(I,1)
460  CONTINUE
465  XD=XD+H
466  X=XD
      IF (MK .EQ. 3) MK=0
      CALL DERIV(X,Y,D)
      DO 470 I=1,N
      DM(I,MK+1)=D(I)
470  CONTINUE
      FP=F
      CALL TERM (X,Y,D,F)
C-----DO YOU TERMINATE
500  IF (ABS(F) .LE. EP6) GO TO 800
      IF (FP .EQ. 0.) GO TO 510
      IF (NRET .NE. M4 .OR. F*FP .LT. EP11) GO TO 805
510  XS=XD
      IF (MK .NE. 0 .AND. H .EQ. HN) MK=MK+1
C-----DO YOU PRINT
600  NPR=NPR+1
      IF (MPR .LE. 0) GO TO 610
      IF (NPR .GE. MPR) GO TO 50
      GO TO 100
610  IF (ABS(Y(N+1)-PC) .GE. Y(N+2)) GO TO 50
      GO TO 100
C-----DETERMINING THE STEP SIZE
700  HB = HMAX5
      DO 760 I = 1,N
      Z=ABS(ERROR(I))
      IF (YC(I) .EQ. 0.) GO TO 720
      ZZ=YC(I)
      ZZ=ABS(ZZ)
      IF (EC) 720,710,705
705  IF (EC .GT. ZZ) ZZ=EC
710  Z=Z/ZZ
720  IF (Z.GT.ELO.AND.Z.LT.EUP) GOTO 750
      HB = AMIN1(HB,EM/(Z+EP11))
      GOTO760
750  HB=AMIN1(HB,1.)
760  CONTINUE
      IF (HB .NE. 1.) GO TO 765
      NHTS=0
      GO TO 450
765  HN=H*HB**.2
      IF (MK .NE. 1) JTEST=1

```



## APPENDIX D CONTINUED

```

MK=1
IF (HB.LT.1.) GOTO 770
IF (ABS(HN) .GT. ABS(4.*H)) HN=4.*H
NHTS=0
GOTO 450
770 HEPS=ABS(X*EP6) + EP11
IF (ABS(HN) .LT. ABS(H/4.)) HN=H/4.
IF (ABS(HN) .GT. HEPS) GO TO 790
NHTS = NHTS + 1
IF (NHTS .LE. 10) GO TO 780
NRET = 1
GO TO 450
780 HN=SIGN(HEPS,HN)
IF (NHTS .GT. 1) GO TO 450
790 IF (NHTS .GT. 1) NHTS=0
IF (JAM .EQ. 0) GO TO 100
DO 795 I=1,N
YD(I)=YK(I)
795 CONTINUE
XD=XDS
JTEST=1
GO TO 100
C-----THE TERMINATION LOOP
800 NRET=0
805 IF (NRET .LT. 0) GO TO 806
H=XD-XS
GO TO 50
806 IF (F*FP.LT.0.) GOTO 810
IF (F*FP2.LT.0.) GOTO 820
GO TO 800
810 FP2 =FP
HP =H
GOTO 830
820 FP =FP2
HP =H + HP
830 NRET=NRET+1
H=HP*F/(FP-F)
JTEST=4
GOTO 300
END
```



APPENDIX E

FNOL3 VS. FNOL2

E-1. FNOL3 does not allow the step size to be changed by more than a factor of four. In FNOL2, the step size is allowed to change by any factor, which can cause the step size to be too large or too small in some cases.

E-2. If the step size is too small, FNOL3 accepts the step and the step size is increased for the next step. FNOL2 does not accept the step.

E-3. FNOL3 calls the output routine only if the step was accepted. FNOL2 calls the output routine and then checks to see if the step is acceptable.

E-4. In FNOL3, the truncation errors are added at each step to the dependent variables. FNOL2 does not add the truncation errors to the dependent variables.

E-5. FNOL3 allows the step size to be changed when using the Runge-Kutta method. The step size cannot be changed using the Runge-Kutta method in FNOL2.

E-6. In FNOL3, the option was added that if relative error is used to adjust the step size and the user sets  $Y(N+3)=\epsilon$  ( $\epsilon > 0$ ), then whenever  $|Y(I)| < Y(N+3)$ , relative error is calculated by dividing truncation error by  $Y(N+3)$  rather than  $Y(I)$ . Otherwise perfect accuracy would be required of every variable passing through 0.

E-7. FNOL3 uses XNE, a floating point rather than an integer, to allow more control over the step size.



## APPENDIX F

FNOL3 ARGUMENT LIST SUMMARY

<u>ARGUMENT</u>	<u>TYPE</u>	<u>INPUT</u>	<u>OUTPUT</u>	<u>REMARKS</u>
J	INTEGER	YES	_____	The integration method
N	INTEGER	YES	_____	The number of equations
G	REAL	YES	_____	The initial step size
L	INTEGER	YES	_____	The additional output Y's
M	INTEGER	YES	_____	The print frequency
XNE	REAL	YES	_____	The control for step size
X	REAL	YES	YES	The independent variable
Y	REAL	YES	YES	The dependent variables
D	REAL	NO	YES	The derivatives
DERIV	_____	_____	_____	CALL DERIV(X,Y,D)
TERM	_____	_____	_____	CALL TERM(X,Y,D,T)
OUTPUT	_____	_____	_____	CALL OUTPUT(X,Y,D,ERROR,N,L,H)



MATHEMATICS DEPARTMENT  
EXTERNAL DISTRIBUTION LIST

Copies

Commander, Naval Air Systems Command  
Department of the Navy  
Washington, D.C. 20360  
Attn: Code 604  
Attn: Code 03D  
Attn: Code 5203

Commander, Naval Ordnance Systems Command  
Department of the Navy  
Washington, D.C. 20360  
Attn: Code 9132  
Attn: Code 03A  
Attn: Code 0322  
Attn: Code 083213 (Boucher)

2

Director, Special Projects  
Department of the Navy  
Washington, D.C. 20360  
Attn: SP-2722

Commander, Naval Ship Systems Command  
Department of the Navy  
Washington, D.C. 20360  
Attn: Code 031 (J. H. Huth)

Chief, Defense Atomic Support Agency  
Washington, D.C. 20390  
Attn: Document Library Branch

2

Commanding General  
Aberdeen Proving Ground, Maryland 21005  
Attn: Technical Information Branch  
Attn: Director, Ballistic Research Laboratories

2

2

Defense Documentation Center  
Cameron Station  
Alexandria, Virginia 22314

20

Commanding Officer and Director  
Aerodynamics Laboratory  
Naval Ship Research and Development Center  
Washington, D.C. 20007  
Attn: Library

Commanding Officer and Director  
Applied Mathematics Laboratory  
Naval Ship Research and Development Center  
Washington, D.C. 20007  
Attn: Dr. D. Shanks  
Attn: Library  
Attn: J. A. Blalock

Commanding Officer  
Harry Diamond Laboratory  
Washington, D.C. 20438  
Attn: Library, Bldg. 92, Rm. 211

Director of Intelligence  
Headquarters, USAF  
Washington, D.C. 20390  
Attn: AFOIN-3B

NASA  
Langley Research Center  
Langley Field, Virginia 23365  
Attn: Theoretical Aerodynamic Division  
Attn: Librarian

NASA  
Ames Research Center  
Moffett Field, California 94035  
Attn: Librarian

NASA  
High Speed Flight Station  
Edwards, California 93523  
Attn: Library

NASA  
Lewis Research Center  
21000 Brookpark Road  
Cleveland, Ohio 44134  
Attn: Librarian  
Attn: Chief, Propulsion and Aerodynamic Division

Commander  
Pacific Missile Range  
Point Mugu, California 93041  
Attn: Technical Library  
Attn: C. J. Thorne  
Attn: J. C. Alexander

National Bureau of Standards  
Washington, D.C. 20390  
Attn: Applied Mathematics Division  
Attn: Library



Commander  
U. S. Naval Ordnance Test Station  
China Lake, California 93555  
Attn: Technical Library  
Attn: Code 406  
Attn: Code 507  
Attn: Code 5019  
Attn: A. A. Fojt

Commander  
U. S. Naval Weapons Laboratory  
Dahlgren, Virginia 22448  
Attn: Technical Library  
Attn: E. C. Hubbard

Director  
Naval Research Laboratory  
Code 2029 (ONRL)  
Washington, D.C. 20390  
Attn: Library

Office of Naval Research  
800 N. Quincy Street  
Arlington, Virginia 22217  
Attn: Head, Mathematics Program  
Attn: Dr. Stuart L. Brodsky, Code 432

Naval Research Laboratory  
Washington, D.C. 20390  
Attn: Technical Documents  
Attn: Code 2027

Oak Ridge National Laboratory  
Oak Ridge, Tennessee 37830  
Attn: Dr. A. S. Householder  
Attn: Library

Commander  
Naval Ordnance Laboratory  
Corona, California 91720  
Attn: A. Sevy

Commander  
Naval Missile and Astronautics Center  
Point Mugu, California 93041  
Attn: C. A. Kent

Office of Assistant Secretary of Defense (R&D)  
Room 3E1065, The Pentagon  
Washington, D.C. 20390  
Attn: Technical Library

Headquarters, Arnold Engineering Development Center  
Air Research and Development Center  
Arnold Air Force Station, Tennessee 37389  
Attn: Technical Library

Commanding General  
Redstone Arsenal  
Huntsville, Alabama 35806  
Attn: Technical Library

Hughes Aircraft Company  
Florence Avenue at Teale Street  
Culver City, California 90230  
Attn: Mr. Dana H. Hohnson  
R&D Technical Library

McDonnell Aircraft Corporation  
P.O. Box 516  
St. Louis, Missouri 63166  
Attn: Engineering Library  
Department 644

United Aircraft Corporation  
400 Main Street  
East Hartford, Connecticut 06118  
Attn: Chief Librarian

Superintendent  
U. S. Naval Postgraduate School  
Monterey, California 93940  
Attn: Library, Technical Reports Section

California Institute of Technology  
Pasadena, California 91109  
Attn: Aeronautics Department

Aero Engineering Department  
University of Maryland  
College Park, Maryland 20740  
Attn: Prof. A. Wiley Sherwood

Lockheed Missiles and Space Company  
P.O. Box 504  
Sunnyvale, California 94088  
Attn: Technical Information Center

Guggenheim Aeronautical Laboratory  
California Institute of Technology  
Pasadena, California 91109  
Attn: Aeronautics Library

University of California  
Berkeley, California 94720  
Attn: Dr. S. A. Schaaf

University of California  
Los Angeles, California 90024  
Attn: Prof. M. R. Hestenes

California Institute of Technology  
Pasadena, California 91109  
Attn: Library

Jet Propulsion Laboratory  
California Institute of Technology  
Pasadena, California 91109  
Attn: Library  
Dr. E. C. Posner

Mathematics Research Center  
U. S. Army  
University of Wisconsin  
Madison, Wisconsin 53706  
Attn: S. J. Kleene  
E. Zarantonello

Case Institute of Technology  
Cleveland, Ohio 10900  
Attn: Prof. G. Kuerti

Cornell University  
Graduate School of Aeronautical Engineering  
Ithaca, New York 14850  
Attn: Prof. W. R. Sears

Applied Physics Laboratory  
Johns Hopkins University  
8621 Georgia Avenue  
Silver Spring, Maryland 20910  
Attn: Dr. N. H. Choksy  
C. V. Bitterli  
Dr. S. Haywood

Chairman  
Engineering and Applied Sciences  
California Institute of Technology  
Pasadena, California 91109

Mathematics Department  
Harvard University  
Cambridge, Massachusetts 02138  
Attn: Prof. G. Birkhoff

Institute for Fluid Dynamics and Applied Mathematics  
University of Maryland  
College Park, Maryland 20740  
Attn: Prof. M. H. Martin

University of Michigan  
Randall Laboratory  
Ann Arbor, Michigan 48106  
Attn: Prof. Otto Laporte

Supervisor  
Technical Documents Services  
Willow Run Laboratories  
University of Michigan  
Willow Run Airport  
Ypsilanti, Michigan 48197

Applied Mathematics and Statistics Laboratory  
Stanford University  
Stanford, California 94305  
Attn: Prof. G. E. Forsythe

Defense Research Laboratory  
The University of Texas  
P.O. Box 8092  
Austin, Texas 78767  
Attn: H. D. Kirck, Asst. Director

The Avco Manufacturing Corporation  
Research Laboratories  
2385 Revere Beach Parkway  
Everett, Massachusetts 02149

Cornell Aeronautical Laboratory Incorporated  
P.O. Box 235, 4455 Genessee Street  
Buffalo, New York 14225  
Attn: Librarian

Douglas Aircraft Company Incorporated  
Santa Monica Division  
3000 Ocean Park Blvd.  
Santa Monica, California 90405  
Attn: Library

Missile and Ordnance Systems Department  
General Electric Company  
3198 Chestnut Street  
Philadelphia, Pennsylvania 19104  
Attn: L. Chasen, Mgr. Library

Goddard Space Center  
Code 507  
Greenbelt, Maryland 20770  
Attn: Mr. Charles Newman  
Mr. Jerry Linnekin

Smithsonian Institution  
10th and Jefferson Drive  
Washington, D.C. 20560  
Attn: Mr. James Crockett  
Attn: Mr. Dante Piacesi



Unclassified

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Naval Ordnance Laboratory White Oak, Silver Spring, Maryland 20910		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE FNOL3, A Computer Program to Solve Ordinary Differential Equations			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (First name, middle initial, last name) Ralph E. Ferguson Theodore A. Orlow			
6. REPORT DATE 1 March 1971		7a. TOTAL NO. OF PAGES 40	7b. NO. OF REFS 2
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S) NOLTR 71-2	
b. PROJECT NO.			
c.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. DISTRIBUTION STATEMENT This document has been approved for public release and sale, its distribution is unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
13. ABSTRACT FNOL3 is a Fortran IV subprogram which uses fourth order Runge-Kutta and Adams-Moulton methods to solve up to 30 ordinary differential equations with initial conditions. Options allow control of error, step-size, print frequency and integration method. There is a discussion on the integration methods and their error terms. Listings of the subprogram and sample problems and their results as run on NOL's CDC 6400 are included.			

Unclassified

Security Classification





NOL LIBRARY REPORT NUMBER (LIST ONE REPORT ONLY)		DATE REQUESTED	
NOLTR 71-2		12/12/75	
NAME	DIVISION	ROOM NO.	EXT.
Henry M. Ward	WR-15	336-210	4-1169
STATUS OF REQUEST (FOR 730 USE ONLY)			
<input type="checkbox"/> ON LOAN WITHIN NOL AND BEING RECALLED		<input type="checkbox"/> ON MICROFILM - MICROFILM AND READER IN ROOM 1-328	
<input type="checkbox"/> YOUR NAME ADDED TO WAITING LIST		<input type="checkbox"/> REPORTS DESTROYED IN ACCORDANCE WITH NOLINST. 5070.1B	
<input type="checkbox"/> RECALLED FROM STORAGE AVAILABLE		<input type="checkbox"/> OTHER	
(DAYS)		(WEEKS)	
REPORT REQUEST NDW-NOL 5070/21 (REV. 9-66) WHITE COPY-FOR LIBRARY USE YELLOW COPY-FOR REQUESTER'S USE			

DEC 17 1975